

DIESEL GENERATOR SET

WATER CHARGE-AIR COOLING

1030kVA/50 Hz/Prime (Fuel-Optimized)
380 - 415V



Optional equipment shown. Standard equipment may vary.

BENEFITS

- // Low installation costs
- // Best fuel consumption values
- // Long maintenance intervals
- // Best-in-class reliability and availability
- // Lifting vertically or with diagonal pull
- // Compact design

SYSTEM RATINGS^①

Prime	DP01030D5S	DP01030D5S	DP01030D5S
Voltage (L-L)	380V	400V	415V
Phase	3	3	3
PF	0.8	0.8	0.8
Hz	50	50	50
kW	824	824	816
kVA	1030	1030	1020
Amps	1565	1487	1419
Generator model	575RSL7074	575RSL7074	575RSL7074
Temp rise	125 °C/40 °C	125 °C/40 °C	125 °C/40 °C
Connection	6 LEAD HI WYE	6 LEAD HI WYE	6 LEAD HI WYE

^① Power available up to 40°C/400 m

CERTIFICATIONS AND STANDARDS

// Engine-generator set is designed and manufactured in facilities certified to standards ISO 9001:2008 and ISO 14001:2004

// Performance Assurance Certification (PAC)

- Engine-generator set tested according to ISO 8528-5 for transient response
- Verified product design, quality and performance integrity
- All engine systems are type and factory tested

// Power Rating

- Permissible average power output during 24 hours of operation up to 75%

STANDARD EQUIPMENT^①

// Engine

Air filters

Oil pump for draining

Full flow oil filters

Closed crankcase ventilation

Jacket water pump

Thermostats

Exhaust manifold – dry

Belt driven radiator fan

Radiator – unit mounted

Electric starting motor – 24V

Governor – electronic isochronous

Base – formed steel

SAE flywheel & bell housing

Charging alternator

Flexible fuel connectors

Flexible exhaust connection

// Generator

NEMA MG1, IEEE and ANSI standards compliance for temperature rise and motor

VDE 0530, IEC 60034-1, BS4999, BS5000, CSA22.2-100, AS 1365

Sustained short circuit current of up to 250% of the rated current for up to 10 seconds

Self-ventilated and drip-proof IP23

Superior voltage waveform

Digital, volts-per-hertz regulator

No load to full load regulation

Brushless alternator with brushless pilot exciter

4 Pole, rotating field

125 °C maximum prime temperature rise

Heavy duty shielded ball bearings with a minimum B-10 life of 40,000 hrs

Flexible coupling

Full amortisseur windings

3-phase voltage sensing

±0.25% voltage regulation

100% of rated load – one step according to NFPA 110

3% maximum harmonic content

^① Represents standard product only. Consult Factory/MTU Onsite Energy distributor for additional configurations.

STANDARD FEATURES*

- // The engine-generator set complies to G3
- // Engine generator set tested according to ISO 8528-5 for transient response
- // Accepts rated load in one step as per NFPA 110
- // All engine-generator sets are type and factory tested
- // MTU Onsite Energy is a single source supplier
- // Global product support
- // 16V2000 diesel engine (31,84 Liter (1943 cu inch) displacement; 4-stroke)
- // Engine-generator resiliently mounted
- // Complete range of accessories
- // Brushless, rotating field generator (PMG excitation; 250% short circuit capability; 2/3 pitch stator windings)
- // Complete system metering
- // LCD display

APPLICATION DATA

// Engine

Manufacturer	MTU
Model	16V2000G65TB
Type	4-Stroke
Arrangement	16-V
Displacement/cylinder: l (cu inch)	1.99 (121)
Bore: mm (inch)	130 (5.1)
Stroke: mm (inch)	150 (5.9)
Compression ratio	16:1
Rated speed rpm	1500
Engine governor	Electronic isochronous
Max power: kWm (bhp)	890 (1194)
Speed regulation	±0.25%
Air filter	Dry

// Lube Oil Capacity

Total oil system: l (gal)	102 (27)
---------------------------	----------

// Electrical

Electric Volts DC	24
Cold cranking amps under -17.8 °C (0 °F)	1000

// Fuel System

Fuel supply connection size	M22x1,5 - 60°/Male
Fuel return connection size	M12x1,5 - 60°/Male
Maximum fuel lift: m (ft)	5 (16)
Recommended fuel	see MTU fluids & lubrication spec.
Total fuel flow: l/hr (gal/hr)	600 (159)

// Fuel Consumption^②

	gal/hr	l/hr	g/kwh
At 100% of power rating:	57	214	200
At 75% of power rating:	42	158	196
At 50% of power rating:	28	108	201

// Cooling/Radiator System

Water pump capacity: l/min (gpm)	667 (176)
Heat rejection to coolant: kW (BTUM)	375 (21,326)
Heat rejection to after cooler: kW (BTUM)	195 (11,089)
Heat radiated to ambient: kW (BTUM)	45 (2559)
Engine coolant capacity: l (gal)	130 (34)

// Air Requirements^③

Aspirating: m³/min (SCFM)	66 (2328)
---------------------------	-----------

// Exhaust System


Gas temp. (stack): °C (°F)	530 (986)
Gas volume flow	
temp: m³/min (SCFM)	177 (6250)
Maximum allowable back pressure: kPa	8.5

① Represents standard product only. Consult Factory/MTU Onsite Energy distributor for additional configurations.

② Values in accordance with ISO 3046-1. Conversion calculated with fuel density of 0.83 g/ml.

③ Air density = 1.184 kg/m³ (0.0739 lbm/ft³)

WEIGHTS AND DIMENSIONS



Drawing above for illustration purposes only, based on a standard open power 400 Volt engine-generator set. Lengths may vary with other voltages. Do not use for installation design. See website for unit specific template drawings.

System	Dimensions (L x W x H)	Weight (dry/less tank)
Open Power Unit (OPU)	4100 x 1750 x 1809 mm (161.4 x 69 x 71.2 inch)	5945 kg (13,106 lbs)

Weights and dimensions are based on open power units and are estimates only. Consult the factory for accurate weights and dimensions for your specific engine-generator set.

SOUND DATA

// Consult your local MTU Onsite Energy distributor for sound data.

EMISSIONS DATA

// Consult your local MTU Onsite Energy distributor for emissions data.

RATING DEFINITIONS AND CONDITIONS

// Prime power ratings apply to installations where utility power is unavailable or unreliable. At varying load, the number of generator set operating hours is unlimited. A 10% overload capacity is available for one hour in twelve. Ratings are in accordance with ISO-8528-1, overload power in accordance with ISO-3046-1, BS 5514, AS 2789, and DIN 6271. For limited running time and base load ratings, consult the factory.

// Deration factor:

Altitude: Consult your local MTU Onsite Energy distributor for altitude derations.

Temperature: Consult your local MTU Onsite Energy distributor for temperature derations.

Materials and specifications subject to change without notice.