


# DIESEL GENERATOR SET

## DP02500D5S

380V – 11 kV/50 Hz/Prime/NEA (ORDE) Optimized  
MTU 20V4000G23/Water Charge Air Cooling



Optional equipment and finishing shown. Standard may vary.

### PRODUCT HIGHLIGHTS

#### // Benefits

- Low fuel consumption
- Optimized system integration ability
- High reliability
- High availability of power
- Long maintenance intervals

#### // MTU Onsite Energy is a single-source supplier

#### // Support

- Global product support offered

#### // Standards

- Engine-generator set is designed and manufactured in facilities certified to standards ISO 2008:9001 and ISO 2004:14001
- Generator set complies to ISO 8528
- Generator meets NEMA MG1, BS5000, ISO, DIN EN and IEC standards
- NFPA 110

#### // Power Rating

- System ratings: 2500 kVA - 2600 kVA
- Accepts rated load in one step per NFPA 110
- Generator set complies to G3 according to ISO 8528-5
- Generator set exceeds load steps according to ISO 8528-5

#### // Performance Assurance Certification (PAC)

- Engine-generator set tested to ISO 8528-5 for transient response
- 75% load factor
- Verified product design, quality and performance integrity
- All engine systems are prototype and factory tested

#### // Complete range of accessories available

- Control panel
- Circuit breaker/power distribution
- Fuel system
- Fuel connections with shut-off valve mounted to base frame
- Starting/charging system
- Exhaust system
- Mechanical and electrical driven radiators
- Medium voltage alternators

#### // Emissions

- NEA (ORDE) optimized

#### // Certifications

- CE certification option

APPLICATION DATA<sup>①</sup>

## // Engine

Manufacturer	MTU
Model	20V4000G23
Type	4-cycle
Arrangement	20V
Displacement: l	95.4
Bore: mm	170
Stroke: mm	210
Compression ratio	16.4
Rated speed: rpm	1500
Engine governor	ADEC
Max power: kWm	2420
Air cleaner	Dry

## // Fuel System

Maximum fuel lift: m	5
Total fuel flow: l/min	27

// Fuel Consumption<sup>②</sup>

	l/hr	g/kwh
At 100% of power rating:	580.2	199
At 75% of power rating:	457.0	209
At 50% of power rating:	320.7	220

## // Liquid Capacity (Lubrication)

Total oil system capacity: l	390
Engine jacket water capacity: l	205
System coolant capacity: l	50

## // Combustion Air Requirements

Combustion air volume: m <sup>3</sup> /s	2.4
Max. air intake restriction: mbar	50

## // Cooling/Radiator System

Coolant flow rate (HT circuit): m <sup>3</sup> /h	80
Coolant flow rate (LT circuit): m <sup>3</sup> /h	32.5
Heat rejection to coolant: kW	930
Heat radiated to charge air cooling: kW	350
Heat radiated to ambient: kW	105
Fan power for mech. radiator (40°C): kWm	70

## // Exhaust System

Exhaust gas temp. (after turbocharger): °C	540
Exhaust gas volume: m <sup>3</sup> /s	6.5
Maximum allowable back pressure: mbar	85
Minimum allowable back pressure: mbar	30

① All data refers only to the engine and is based on ISO standard conditions (25°C and 100m above sea level).

② Values referenced are in accordance with ISO 3046-1. Conversion calculated with fuel density of 0.83 g/ml.  
All fuel consumption values refer to rated engine power.

## STANDARD AND OPTIONAL FEATURES

### // System Ratings (kW/kVA)

Generator model	Voltage	NEA (ORDE) optimized 40°C/100m								
		without radiator			with mechanical radiator			with electr. driven radiator		
		kWel	kVA*	AMPS	kWel	kVA*	AMPS	kWel	kVA*	AMPS
Marathon 1020FDL7093 (Low voltage marathon standard)	380 V	2080	2600	3950	2040	2550	3874	2040	2550	3874
	400 V	2080	2600	3753	2000	2500	3608	2000	2500	3608
	415 V	2080	2600	3617	2000	2500	3478	2000	2500	3478
Marathon 1030FDL7094 (Low voltage marathon oversized)	380 V	2080	2600	3950	2040	2550	3874	2040	2550	3874
	400 V	2080	2600	3753	2000	2500	3608	2000	2500	3608
	415 V	2080	2600	3617	2000	2500	3478	2000	2500	3478
Leroy Somer LSA 53.1 M80 (Low voltage Leroy Somer)	380 V	2080	2600	3950	2040	2550	3874	2040	2550	3874
	400 V	2080	2600	3753	2040	2550	3681	2040	2550	3681
	415 V	2080	2600	3617	2040	2550	3548	2040	2550	3548
Marathon 1030FDH7101 (Medium volt. marathon)	11 kV	2080	2600	136	2000	2500	131	2040	2550	134
Leroy Somer LSA 54 XL75 (Medium volt. Leroy Somer)	11 kV	2080	2600	136	2040	2550	134	2040	2550	134

\* cos phi = 0,8

### // Engine

- 4-Cycle
- Standard single stage air filter
- Oil drain extension & shut-off valve
- Closed crankcase ventilation
- Governor-electronic isochronous
- Common rail fuel injection
- NEA (ORDE) optimized engine

### // Generator

- NEMA MG1, BS5000, ISO, DIN EN and IEC standards
- Self-ventilated
- Superior voltage waveform
- Solid state, volts-per-Hertz regulator
- No load to full load regulation
- ±0,25% voltage regulation no load to full load
- Brushless alternator with brushless pilot exciter
- 4 pole, rotating field
- Sustained short circuit current of up to 250% of the rated current for up to 10 seconds (marathon generator)
- Sustained short circuit current of up to 300% of the rated current for up to 10 seconds (Leroy Somer generator)
- Marathon low voltage generator
- Leroy Somer generator (please contact your local MTU Onsite Energy distribution partner for system ratings)
- Oversized generator
- Medium voltage generator

### // Cooling System

- Jacket water pump
- Thermostat(s)
- Water charge air cooling
- Mechanical radiator
- Electrical driven front-end cooler
- Jacket water heater

Represents standard features

Represents optional features

## STANDARD AND OPTIONAL FEATURES, CONTINUATION

### // Control Panel

- |   |  |   |
|---|--|---|
| <ul style="list-style-type: none"> <li><input checked="" type="checkbox"/> Pre-wired control cabinet for easy application of customized controller (V1+)</li> <li><input type="checkbox"/> Island operation (V2)</li> <li><input type="checkbox"/> Automatic mains failure operation with ATS (V3a)</li> <li><input type="checkbox"/> Automatic mains failure operation incl. control of generator and mains breaker (V3b)</li> <li><input type="checkbox"/> Island parallel operation of multiple gensets (V4)</li> <li><input type="checkbox"/> Automatic mains failure operation with short (&lt; 10s) mains parallel overlap synchronization (V5)</li> <li><input type="checkbox"/> Mains parallel operation of a single genset (V6)</li> <li><input type="checkbox"/> Mains parallel operation of multiple gensets (V7)</li> </ul> | <ul style="list-style-type: none"> <li><input type="checkbox"/> Basler controller</li> <li><input type="checkbox"/> Deif controller</li> <li><input checked="" type="checkbox"/> Complete system metering</li> <li><input checked="" type="checkbox"/> Digital metering</li> <li><input checked="" type="checkbox"/> Engine parameters</li> <li><input checked="" type="checkbox"/> Generator Protection Functions</li> <li><input checked="" type="checkbox"/> Engine protection</li> <li><input checked="" type="checkbox"/> SAE J1939 engine ECU communications</li> <li><input checked="" type="checkbox"/> Parametrization software</li> <li><input checked="" type="checkbox"/> Multilingual capability</li> <li><input checked="" type="checkbox"/> Multiple programmable contact inputs</li> <li><input checked="" type="checkbox"/> Multiple contact outputs</li> <li><input checked="" type="checkbox"/> Event recording</li> <li><input checked="" type="checkbox"/> IP 54 front panel rating with integrated gasket</li> </ul> | <ul style="list-style-type: none"> <li><input type="checkbox"/> Different expansion modules</li> <li><input type="checkbox"/> Remote annunciator</li> <li><input type="checkbox"/> Daytank control</li> <li><input type="checkbox"/> Generator winding temperature monitoring</li> <li><input type="checkbox"/> Generator bearing temperature monitoring</li> <li><input type="checkbox"/> Differential protection with multi-function protection relay</li> <li><input type="checkbox"/> Modbus RTU-TCP gateway</li> </ul> |
|---|--|---|

### // Circuit Breaker/Power Distribution

- |  |  |  |
|--|--|--|
| <ul style="list-style-type: none"> <li><input type="checkbox"/> 3-pole circuit breaker</li> <li><input type="checkbox"/> 4-pole circuit breaker</li> </ul> | <ul style="list-style-type: none"> <li><input type="checkbox"/> Manual-actuated circuit breaker</li> <li><input type="checkbox"/> Electrical-actuated circuit breaker</li> </ul> | <ul style="list-style-type: none"> <li><input type="checkbox"/> Stand-alone solution in separate switch box</li> </ul> |
|--|--|--|

### // Fuel System

- |   |   |
|---|---|
| <ul style="list-style-type: none"> <li><input checked="" type="checkbox"/> Flexible fuel connectors mounted to base frame</li> <li><input type="checkbox"/> Fuel filter with water separator</li> <li><input type="checkbox"/> Switchable fuel filter with water separator</li> </ul> | <ul style="list-style-type: none"> <li><input type="checkbox"/> Seperate fuel cooler</li> <li><input type="checkbox"/> Fuel cooler integrated into cooling equipment</li> </ul> |
|---|---|

### // Starting/Charging System

- |   |  |
|---|--|
| <ul style="list-style-type: none"> <li><input checked="" type="checkbox"/> 24V starter</li> <li><input type="checkbox"/> Starter batteries</li> </ul> | <ul style="list-style-type: none"> <li><input type="checkbox"/> Battery rack &amp; cables</li> <li><input type="checkbox"/> Battery charger</li> </ul> |
|---|--|

## STANDARD AND OPTIONAL FEATURES, CONTINUATION

---


### // Mounting System

- Welded base frame
- Resilient engine and generator mounting
- Modular base frame design

### // Exhaust System

- Exhaust bellows with connection flange
- Exhaust silencer with 10 dB(A) sound attenuation
- Exhaust silencer with 30 dB(A) sound attenuation
- Exhaust silencer with 40 dB(A) sound attenuation
- Y-connection-pipe

## WEIGHTS AND DIMENSIONS



Drawing above for illustration purposes only, based on a standard open power 400 Volt engine-generator set. Lengths may vary with other voltages. Do not use for installation design. See website for unit specific template drawings.

System	Dimensions (LxWxH)	Weight (dry/less tank)
Open Power Unit (OPU)	6176 x 1810 x 2332 mm	18339 kg

Weights and dimensions are based on open power units and are estimates only. Consult the factory for accurate weights and dimensions for your specific engine-generator set.

## SOUND DATA

// Consult your local MTU Onsite Energy distributor for sound data.

## EMISSIONS DATA

// Consult your local MTU Onsite Energy distributor for emissions data.

## RATING DEFINITIONS AND CONDITIONS

// Prime power ratings apply to installations where utility power is unavailable or unreliable. At varying load, the number of generator set operating hours is unlimited. A 10% overload capacity is available for one hour in twelve. Ratings are in accordance with ISO 8528-1, ISO 3046-1, BS 5514, AS 2789 and DIN 6271. Average load factor: < 75%.

// Deration factor:

Altitude: Consult your local MTU Onsite Energy Power Generation distributor for altitude derations.

Temperature: Consult your local MTU Onsite Energy Power Generation distributor for temperature derations.

Rated power is available up to 40°C and 100m above sea level.

Materials and specifications subject to change without notice.